



KEYSTONE

Dijon Tile Range Data Sheet

Product technical details – compliant with standards EN 14411:2012

Tile Sizes	Tile Colours
600 x 900 x 10mm Rectified Natural	All colours all sizes (Grey, Gold, Pearl)
600 x 900 x 20mm Rectified Natural	
Skirting 65 x 900 x 10mm Rectified Natural	

Grey



Gold



Pearl



sales@keystoneco.co.uk



204 Duggins Lane, Coventry, CV4 9GP.



www.keystoneco.co.uk



024-76422-580



KEYSTONE

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	0,05%
Breaking Strength	ISO 10545-4	≥ 1300 N	CONFORM
Modulus of Rupture	ISO 10545-4	≥ 35 N/mm ²	≥ 35 N/mm²
Durability: Internal	EN 14411:2012		Passed
Durability: External	EN 14411:2012		Passed
Thermal Shock Resistance	EN 14411:2012		Passed
Adhesion Resistance			
- Cementitious adhesive C1 class	EN 14411:2012		≥ 0,5 N/mm²
- Cementitious adhesive C2 class	EN 14411:2012		≥ 1,0 N/mm²
Chemical Resistance	ISO 10545-13	As indicated by manufacturer	UNAFFECTED
Frost Resistance	ISO 10545-12	No alteration	FROST PROOF
Slip Resistance	DIN 51130 / R-DIN 51097	-	R10 Naturale R10 /"B"
	DIN 51130 / R-DIN 51097		Grip: R11 / C
Length & Width *			
Shade Variation		As indicated by manufacturer	V2 Slight variations
Fire Reaction	EN 14411:2012		Class A1 (wall) Class A1fl (floor)
Recommended minimum joint Interior/Exterior		RECT (Interior) Outdoor	2mm 5-6mm circa/approx

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

*(Please note rectified tiles are reduced in size during the rectification process but the size is consistent from tile to tile to the following specification. E.g.600mm x 300mm tile rectified will be 595mm x 295mm)



sales@keystoneco.co.uk



204 Duggins Lane, Coventry, CV4 9GP.



www.keystoneco.co.uk



024-76422-580