

PEAK EDGE


TECHNICAL SPECIFICATION



This Range

Beautiful range of porcelain tiles, suitable for interior and exterior applications, in a 20mm, 9.5mm & 10.5mm thickness.


Suitable for:



Exterior



Heavy Footfall



Pool Edging




Stairs

Sizes

1800 x 300 x 10.5mm rectified natural
 1800 x 200 x 10.5mm rectified natural
 1200 x 200 x 10.5mm rectified natural
 1200 x 400 x 20mm rectified grip
 mosaic chevron 980 x 200 x 9.5mm rectified natural
 600 x 600 x 9.5mm recitified natural
 600 x 65 x 9.5mm rectified natural
 skirting 600 x 75 x 10mm rectified natural

Colours



Baslow




Mosaic Versailles in Baslow



Burbage



Pattern Print Versailles in Burbage



Derwent



Mosaic Versailles in Derwent



Stanage



Pattern Print Versailles in Stanage

Technical Details - 20, 10.5 & 9.5mm

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	Compliant
Modulus of rupture	ISO 10545-4	≥ 35 N/mm ²	50 N/mm²
Deep Abrasion Resistance	ISO 10545-6	≤ 175 mm ³	145 mm³
Linear Thermal Expansion	ISO 10545-8	No provision	α ≤ 7 x10⁻⁶ °C⁻¹
Stain Resistance	ISO 10545-14	Classe / Class 3 Min.	Class 5
Chemical Resistance (*)	ISO 10545-13	As indicated by manufacturer	Compliant
Frost Resistance	ISO 10545-12	No alteration	Resistant
Slip Resistance	BS 7976:2002	Declared value	R10 Natural R11 Structured
Thickness	ISO 10545-2	+/-0.5	Compliant
Shade Variation		As indicated by manufacturer	Moderate Variation

Recommended minimum joint (**)		RECT (Interior)	2mm (RECT) circa/approx
--------------------------------	--	-----------------	--------------------------------

(*) Excluding hydrofluoric acid and its derivatives. (**) The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards.

Packing Details

Size	Pz/Box	Kg/Box	Mq/Box	Box/Pal	Kg/Pal	Mq/Pal
1200 x 200 x 10.5mm Rectified	6	30	1.44	24	720	34.56
1800 x 200 x 10.5mm Rectified	3	25.5	1.08	48	1224	51.84
1800 x 300 x 10.5mm Rectified	2	25.5	1.08	36	918	38.88
1200 x 400 x 20mm Rectified	2	43.5	0.96	24	1044	23.04
600 x 600 x 9.5mm rectified	4	32	1.44	28	896	40.32
mosaic chevron 980 x 200 x 9.5mm	4	16	.55	30	480	23.52
600 x 65 x 9.5mm	15	11	0.585	60	696.6	32.4
skirting 600 x 75 x 10mm rectified	12	11.61	-	--	-	-



Baslow

Derwent





Burbage

Storage





204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk

