

# PRY-2CM

TECHNICAL SPECIFICATION



# This Range

Beautiful range of porcelain tiles, suitable for outdoor applications, in 20mm thickness.

Suitable for:




Heavy Footfall



Pool Edging



Stairs



Paving


Sizes

900 x 600 x 20mm Rectified  
600 x 600 x 20mm Rectified


Colours



Prysand



Prygrey



Pygraphite

# Technical Details - 20mm

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	<b>Compliant</b>
Breaking Strength	ISO 10545-4	≥ 2500N	<b>Compliant</b>
Modulus of Rupture	ISO 10545-6	≤ 40N/mm <sup>2</sup>	<b>Compliant</b>
Surface Abration	ISO 10545-8	Sand Grey Graphite	<b>Class4</b> <b>Class4</b> <b>Class3</b>
Stain Resistance	ISO 10545-14	Classe / Class 3 Min.	<b>Compliant</b>
Chemical Resistance (*)	ISO 10545-13	As indicated by manufacturer	<b>Compliant</b>
Frost Resistance	ISO 10545-12	No alteration	<b>Resistant</b>
Slip Resistance	BS 7976:200 2	Declared value	+68ptv
Thickness	ISO 10545-2	+/-0.5	<b>Compliant</b>

(\*) Excluding hydrofluoric acid and its derivatives. (\*\*) The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards.

## Packing Details

Size	No./ Pal	Kg/Pal	Mq/Pal
900 x 600 x 20mm Rectified	42	1085	22.49
600 x 600 x 20mm rectified	62	1075	22.32



**PrySand**

**PryGrey**





**PryAnthracite**



204 Duggins Lane, Tile Hill, Coventry,  
CV4 9GP  
02475 092 859  
[www.keystoneco.co.uk](http://www.keystoneco.co.uk)

