



HARRIET

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tiles, suitable for interior applications. Available in 8.5mm, offering a balance of elegance and durability.

Sizes

1000 x 1000 x 8.5mm rectified natural
600 x 600 x 8.5mm rectified natural
600 x 300 x 8.5mm rectified natural
600 x 300 x 8.5mm rectified grip



Heavy Footfall



Stairs



Interior



Wet Areas



Pool Edging


Colours




Cream




Silver



Grey






Taupe



Black

Canvas

	Cream		Silver
	Grey		Taupe
	Black		

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$E_b \leq 0,5\%$ - individual 0,6%	conforms to standard
Modulus of Rupture	ISO 10545-4	minimum 35 N/mm ² - minimum single 32 N/mm ²	> 38 N/mm ²
Thermal Shock Resistance	10545-9	Required	Resistant
Frost resistance	10545-12	Required	Resistant
Chemical resistance	ISO 10545-13	group B minimum	conforms to standard



- Harriet Silver
(Wall)
- Harriet Black
(Floor)



- Harriet Cream Canvas
(Wall)
- Harriet Taupe
(Floor)



**-Harriet Taupe
(Floor)**



**-Harriet Taupe Canvas
(Wall)**



**-Harriet Taupe
(Floor)**



**-Harriet Cream
(Wall)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk

