



SPECTRUM

TECHNICAL SPECIFICATION




Beautiful range of porcelain tiles, suitable for interior and exterior applications, in 6 & 8mm thickness.

Suitable for:




Heavy Footfall



Pool Edging



Stairs



Exterior

Sizes

2700 x 1200 x 6mm rectified natural
 1200 x 1200 x 8mm rectified natural
 1200 x 600 x 8mm rectified natural
 600 x 600 x 8mm rectified natural

Colours

	White		Rouge
	Silver		Steel
	Blush		Feldgrau
	Tan		Marigold
	Teal		Greige
	Tawny		Saddle
	Orange		Espresso

Technical Details - 9.5 & 20mm

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	Compliant
Modulus of breaking	ISO 10545-4	≥ 35 N/mm ²	Compliant
Deep Abrasion Resistance	ISO 10545-6	≤ 175 mm ³	140mm³
Linear Thermal Expansion	ISO 10545-8	No provision	6,5x10⁻⁶ °C⁻¹
Stain Resistance	ISO 10545-14	Class 35Min.	Compliant
Chemical Resistance (*)	ISO 10545-13	As indicated by manufacturer	Compliant
Frost Resistance	ISO 10545-12	No alteration	Resistant
Slip Resistance	BS 7976:2002	Declared value	R10 Natural
Thickness	ISO 10545-2	+/-0.5	Compliant

Recommended minimum joint (**)		RECT (Interior)	2mm (RECT) circa/approx
--------------------------------	--	-----------------	--------------------------------

(*) Excluding hydrofluoric acid and its derivatives. (**) The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards.

Packing Details

Size	Pz/Box	Mq/Box	Box/Pal	Mq/Pal
2700 x 1200 x 6mm			13	
1200 x 1200 x 8mm Rectified	2	2.88	14	40.32
1200 x 600 x 8mm Rectified	2	1.44	30	43.2
600 x 600 x 8mm rectified	4	1.44	32	46.08



White

Silver





Blush

Teal





Tawny

Tawny 2





Orange

Rouge





Steel

Feldgrau





Marigold

Greige





Saddle

Blush 2





204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk

