



TEVERE


TECHNICAL SPECIFICATION



This Range

Limestone effect porcelain, with natural and grip finish. Flowing from inside to outside, with 10mm and 20mm thickness. A tumbled edge for that quality natural stone look. From Cream to Coal, extending the colour palette.


Suitable for:



Exterior



Heavy Footfall



Pool Edging



Stairs

Sizes

900 x 600 x 10.5mm rectified natural
 600 x 600 x 10.5mm rectified natural
 600 x 300 x 10.5mm rectified natural
 900 x 600 x 10.5mm vintage natural
 600 x 600 x 10.5mm vintage natural
 600 x 300 x 10.5mm vintage natural
 900 x 600 x 20mm rectified grip
 600 x 600 x 10mm rectified grip
 skirting 900 x 75 x 10.5mm rectified natural
 skirting 600 x 75 x 10.5mm rectified natural
 modular 1 (900 x 600 x 10.5mm, 600 x 600 x 10.5mm,
 600 x 300 x 10.5mm) natural
 modular 2 (900 x 600 x 10.5mm, 600 x 600 x 10.5mm,
 600 x 300 x 10.5mm) natural
 modular 3 (900 x 600 x 10.5mm, 600 x 600 x 10.5mm,
 600 x 300 x 10.5mm, 300 x 300 x 10.5mm)
 mosaics 300 x 300 x 10.5mm (25mm x 25mm) natural

Colours Available in:

Silver, Cream, Coal

Colours



Coal



Cream



Silver



Mosaic

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0,5%	0,05%
Breaking Strength	ISO 10545-4	≥ 1300 N	CONFORM
Modulus of Rupture	ISO 10545-4	≥ 35 N/mm ²	≥ 35 N/mm²
Durability: Internal	EN 14411:2012		Passed
Durability: External	EN 14411:2012		Passed
Thermal Shock Resistance	EN 14411:2012		Passed
Adhesion Resistance			
- Cementitious adhesive C1 class	EN 14411:2012		≥ 0,5 N/mm²
- Cementitious adhesive C2 class	EN 14411:2012		≥ 1,0 N/mm²
Chemical Resistance	ISO 10545-13	As indicated by manufacturer	UNAFFECTED
Frost Resistance	ISO 10545-12	No alteration	FROST PROOF
Slip Resistance	DIN 51130 / R-DIN 51097		R10 Naturale R10 / "B"
	DIN 51130 / R-DIN 51097		Grip: R11 / C
Length & Width *			
Shade Variation		As indicated by manufacturer	V2 Slight variations
Fire Reaction	EN 14411:2012		Class A1 (wall) Class A1fl (floor)
Recommended minimum joint Interior/Exterior		RECT (Interior) Outdoor	2mm 5-6mm circa/approx



Tevere Coal





Tevere Silver





Tevere Cream





**Tevere Cream
Mosaics
Tevere Silver
20MM Grip**





204 Duggins Lane, Tile Hill, Coventry, CV4 9GP
02475 092 859
www.keystoneco.co.uk

